



SUGGESTED PCB LAYOUT
TOP VIEW

Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 50mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing: Thermoplastic UL 94V-0
 Contact : Selective Gold Plating
 Terminal: 0.35mm Thickness Phosphor Bronze
 Plated With Gold And Tin In Solder Area.
 CUL File No : E215573

PART NO : 6 7 6 4 - B * 1

Positions ———— ↑ ↑ ↑ ↑
 Contacts ———— ↑ ↑
 Housing Color ———— ↑
 Ports ———— ↑ ↑
 Gold Plated
 0 : Gold Flash
 1 : 6u"
 2 : 15u"
 3 : 30u"
 4 : 50u"

 **CHAMPWAY** 冠泰電子有限公司
 CHAMPWAY ELECTRONICS CO., LTD.

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 67 (SERIES)
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
(B)					
(C)					
(D)					
(E)					

TITLE	NON-SHIELDED RJ11		UNIT	mm
圖名	TOP ENTRY PCB JACK		單位	inch
PART NO.	6764-B*1		SCALE	1:1
料號			比例	
REV.	A.1	DATE	2007-12-06	
版本		日期		
CHECKED BY	Michael	DRAWN BY	Chindge	
審核		製圖		