



**Electrical Characteristics :**  
 Insulation Resistance : 500MΩ Min.  
 Contact Resistance : 50mΩ Max.  
 Withstand Voltage : 1000 VAC 1 minute.  
 Current Rating : 1.5A

**Material:**  
 Housing: Thermoplastic UL 94V-0  
 Contact : Selective Gold Plating  
 Terminal: 0.35mm Thickness Phosphor Bronze  
 Plated With Gold And Tin In Solder Area.  
 CUL File No : E215573

**PART NO : 6 6 6 6 - B \* 1**

Positions	↑	↑	↑	↑	Ports
Contacts	↑	↑	↑	↑	
Housing Color					Gold Plated
B : Black					0 : Gold Flash
					1 : 6u"
					2 : 15u"
					3 : 30u"
					4 : 50u"

**CHAMPWAY** 冠泰電子有限公司  
 CHAMPWAY ELECTRONICS CO., LTD.

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 66 (SERIES)	TITLE	6P6C SIDE ENTRY PCB JACK		UNIT	mm
①	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	<b>TOLERANCE(公差) :</b> 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm	圖名			單位	inch
②						PART NO.	6666-B * 1		SCALE	1 : 1
③						料號	REV.	DATE	比例	
④						版本	A.1	2007-01-17		
⑤						CHECKED BY	審核	Michael	DRAWN BY	製圖