

**SUGGESTED PCB LAYOUT
TOP VIEW**

Electrical Characteristics :

- Insulation Resistance : 500MΩ Min.
- Contact Resistance : 30mΩ Max.
- Withstand Voltage : 1000 VAC 1 minute.
- Current Rating : 1.5A


Material:

- Housing : Thermoplastic UL94V-0
- Contact : Full Gold Plating
- Spring Wire : Dia 0.45mm Phosphor Bronze
- Optional Gold Plating Over Nickel
- Shield : Brass, Nickel Plating.

CUL File No : E215573

PART NO : 8 5 0 6 - B * 1 * S

- Positions →
- Contacts →
- Housing Color →
- B : Black
- Gold Plated →
- 0 : Gold Flash
- 1 : 6u"
- 2 : 15u"
- 3 : 30u"
- 4 : 50u"
- Ports →
- For RJ11



ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 85 (SERIES)
(A)					TOLERANCE (公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
(B)					
(C)					
(D)					
(E)					

TITLE 圖名	SHIELDED RJ11 SIDE ENTRY PCB JACK		UNIT 單位	mm inch
PART NO. 料號	8506S-B*1*S		SCALE 比例	1:1
REV. 版本	A.0	DATE 日期	2009-06-22	
CHECKED BY 審核	Michael		DRAWN BY 製圖	Michael