

SUGGESTED PCB LAYOUT
TOP VIEW


Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 30mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 CUL File No : E215573

PART NO : 5 4 6 6 - B * 2

Positions →
 Contacts →
 Housing Color →
 Ports →
 Gold Plated
 0 : Gold Flash
 1 : 6u"
 2 : 15u"
 3 : 30u"
 4 : 50u"
 B : Black

 **CHAMPWAY** 冠泰電子有限公司
 CHAMPWAY ELECTRONICS CO., LTD.

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 54 (SERIES)	TITLE	NON-SHIELDED RJ11 SIDE ENTRY PCB JACK		UNIT	mm	
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm	圖名			單位	inch	
(B)						PART NO.	5466-B*2		SCALE	1:1	
(C)						REV.	A.1	DATE	2007-09-22		
(D)						版本		日期			
(E)						CHECKED BY	Michael		DRAWN BY	David	
						審核		製圖			