


Electrical Characteristics :  
 Insulation Resistance : 500MΩ Min.  
 Contact Resistance : 30mΩ Max.  
 Withstand Voltage : 1000 VAC 1 minute.  
 Current Rating : 1.5A

Material:  
 Housing : Thermoplastic UL94V-0  
 Contact : Full Gold Plating  
 Spring Wire : Dia 0.45mm Phosphor Bronze  
 Optional Gold Plating Over Nickel  
 CUL File No : E215573

PART NO : 6 1 6 6 - B \* 2

Positions →  
 Contacts →  
 Housing Color →  
 Ports →  
 Gold Plated  
 0 : Gold Flash  
 1 : 6u"  
 2 : 15u"  
 3 : 30u"  
 4 : 50u"  
 B : Black

 **CHAMPWAY** 冠泰電子有限公司  
 CHAMPWAY ELECTRONICS CO., LTD.

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 61 (SERIES)	TITLE	DUAL PORTS RJ11		UNIT	mm	
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm	圖名	6P6C SIDE ENTRY PCB JACK		單位	inch	
(B)						PART NO.	6166-B * 2		SCALE	1 : 1	
(C)						REV.	A.1	DATE	2007-01-22		
(D)						版本		日期			
(E)						CHECKED BY	Michael		DRAWN BY	Valiant	
						審核			製圖		