



Electrical Characteristics :
Insulation Resistance : 500MΩ Min.
Contact Resistance : 30mΩ Max.
Withstand Voltage : 1000 VAC 1 minute.
Current Rating : 1.5A

Material:
Housing : Thermoplastic UL94V-0
Contact : Full Gold Plating
Spring Wire : Dia 0.45mm Copper Alloy
Optional Gold Plating Over Nickel
CUL File No : E215573

PART NO : 8 2 6 6 - B ∗ 1 - R

- Positions
- Contacts
- Housing Color
  B : Black
- Ports
- Gold Plated
  0 : Gold Flash
  1 : 6u"
  2 : 15u"
  3 : 30u"
  4 : 50u"





RECOMMENDED PCB LAYOUT
TOP VIEW



CHAMPWAY 冠泰電子有限公司
CHAMPWAY ELECTRONICS CO., LTD.

ZONE	REV.	DESCRIPTION	DATE	APPD.
Ⓐ				
Ⓑ				
Ⓒ				
Ⓓ				
Ⓔ				

FILE NO : 82 (SERIES)

TOLERANCE(公差) :
0.000 mm ± 0.075 mm
0.00 mm ± 0.15 mm
0.0 mm ± 0.25 mm

TITLE 圖 名	RJ11,Unshielded,Receptacle, Horizontal,1x2 Port,THT			UNIT 單位	mm
PART NO. 料 號	8266-B∗1-R			SCALE 比 例	1 : 1
REV. 版本	A.0	DATE 日 期	2011-01-05		
CHECKED BY 審 核	Aaron		DRAWN BY 製 圖	Lucy	