



Electrical Characteristics :  
 Insulation Resistance : 500MΩ Min.  
 Contact Resistance : 30mΩ Max.  
 Withstand Voltage : 1000 VAC 1 minute.  
 Current Rating : 1.5A

Material:  
 Housing : Thermoplastic UL94V-0  
 Contact : Full Gold Plating  
 Spring Wire : Dia 0.45mm Phosphor Bronze  
 Optional Gold Plating Over Nickel  
 CUL File No : E215573

PART NO : 5 3 6 6 - B \* 1

Positions  
 Contacts  
 Housing Color

Ports  
 Gold Plated  
 0 : Gold Flash  
 1 : 6u"  
 2 : 15u"  
 3 : 30u"  
 4 : 50u"

<b>CHAMPWAY</b> 冠泰電子有限公司 CHAMPWAY ELECTRONICS CO., LTD.		TITLE 圖名	RJ11 TOP ENTRY PCB JACK		UNIT 單位	mm inch
		PART NO. 料號	5366-B * 1		SCALE 比例	1 : 1
REV. 版本	A.1	DATE 日期	2007-05-08			
CHECKED BY 審核	Michael		DRAWN BY 製圖	Valiant		

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 53 (SERIES)
Ⓐ	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
Ⓑ					
Ⓒ					
Ⓓ					
Ⓔ					