

**SUGGESTED PCB LAYOUT
TOP VIEW**


Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 50mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 Shield : Brass, Nickel Plating.
 CUL File No : E215573

PART NO : 8 2 8 8 S - B * 2 5 - R

Positions → ↑ ↑ ↑ ↑ ↑
 Contacts → ↑ ↑ ↑ ↑ ↑
 Panel Ground → ↑
 S : 3 Sides With Panel Ground
 Housing Color → ↑
 Ports → ↑ ↑ ↑ ↑ ↑
 Gold Plated
 0 : Gold Flash
 1 : 6u"
 2 : 15u"
 3 : 30u"
 4 : 50u"

 **CHAMPWAY** 冠泰電子有限公司
 CHAMPWAY ELECTRONICS CO., LTD.

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 82 (SERIES)	TITLE	SHIELDED RJ45 SIDE ENTRY PCB JACK		UNIT	mm	
①	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE (公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm	圖名	8288S-B*25-R		單位	inch	
②						料號			SCALE	1:1	
③						版本	A.1	DATE	2007-01-29		
④						日期					
⑤						日期					
						CHECKED BY	Michael		DRAWN BY	Valiant	
						審核			製圖		