

**Electrical Characteristics :**  
 Insulation Resistance : 500MΩ Min.  
 Contact Resistance : 50mΩ Max.  
 Withstand Voltage : 1000 VAC 1 minute.  
 Current Rating : 1.5A

**Material:**  
 Housing: Thermoplastic UL 94V-0  
 Contact : Selective Gold Plating  
 Terminal: 0.35mm Thickness Phosphor Bronze  
 Plated With Gold And Tin In Solder Area.  
 CUL File No : E215573

**PART NO : 8 1 8 8 D N - B \* 2 \* - 0**



Positions  
 Contacts  
 Housing Color  
 B : Black

Led Options  
 Ports  
 Gold Plated  
 0 : Gold Flash  
 1 : 6u"  
 2 : 15u"  
 3 : 30u"  
 4 : 50u"

**LED Color Options Table**

LED Color Options		LED DASH OPTION
LED 2 (Left)	LED 1 (Right)	
No LED	No LED	0
Yellow	Green	1
No LED	Green	2
Yellow	No LED	3
Green	Yellow	4
Green	Green	5
Yellow	Yellow	6
Orange/Green	Orange/Green	7
Yellow/Green	Yellow/Green	8
Orange/Green	Yellow	9
No LED	Green/Yellow	Z
Green	Orange	A
Orange	Green	B
Green	Red	C
Red	Green	D

 **CHAMPWAY** 冠泰電子有限公司  
 CHAMPWAY ELECTRONICS CO., LTD.

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 81 (SERIES)	TITLE	NON-SHIELDED RJ45 WITH LED PCB JACK		UNIT	mm	
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	<b>TOLERANCE(公差) :</b> 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm	圖名			單位	inch	
(B)						PART NO.	8188DN-B*2*-0		SCALE	1:1	
(C)						REV.	A.1	DATE	2007-03-22		
(D)						CHECKED BY	Michael		DRAWN BY	Valiant	
(E)						審核			製圖		