

Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 50mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A


Material:
 Housing: Thermoplastic UL 94V-0
 Contact : Selective Gold Plating
 Terminal: 0.35mm Thickness Phosphor Bronze
 Plated With Gold And Tin In Solder Area.
 CUL File No : E215573

PART NO : 6 6 A 8 8 - B * 1

Positions
 Contacts
 Housing Color
 B : Black

Gold Plated
 0 : Gold Flash
 1 : 6u"
 2 : 15u"
 3 : 30u"
 4 : 50u"

 **CHAMPWAY** 冠泰電子有限公司
 CHAMPWAY ELECTRONICS CO., LTD.

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 66 (SERIES)	TITLE	NON-SHIELDED RJ45 SIDE ENTRY PCB JACK		UNIT	mm
①	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm	圖名			單位	inch
②						PART NO.	66A88-B * 1		SCALE	1 : 1
③						料號	REV.	A.1	DATE	2007-04-13
④						版本	日期			
⑤						CHECKED BY	Michael		DRAWN BY	Valiant
						審核			製圖	