


**SUGGESTED PCB LAYOUT
TOP VIEW**

Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 30mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 Shield : Brass, Nickel Plating.
 CUL File No : E215573

PART NO : 8 2 0 8 S- B * 1 *



CHAMPWAY 冠泰電子有限公司
 CHAMPWAY ELECTRONICS CO., LTD.

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 82 (SERIES)
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE (公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
(B)					
(C)					
(D)					
(E)					

TITLE	SHIELDED RJ45 SIDE ENTRY PCB JACK		UNIT	mm
圖名			單位	inch
PART NO.	8208S-B * 1 *		SCALE	1:1
料號			比例	
REV.	A.1	DATE	2007-01-17	
版本		日期		
CHECKED BY	Michael		DRAWN BY	Valiant
審核			製圖	