

SUGGESTED PCB LAYOUT
TOP VIEW

Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 30mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 CUL File No : E215573

PART NO : 5 2 8 8 - B * *


Positions
 Contacts
 Housing Color
 B : Black

Ports
 Gold Plated
 0 : Gold Flash
 1 : 6u"
 2 : 15u"
 3 : 30u"
 4 : 50u"

Dimensions	No. Of Ports				
	4	5	6	7	8
A	60.9	75.4	89.9	104.4	118.9
B	58.5	73.0	87.5	102.0	116.5
C	43.5	58.0	72.5	87.0	101.5

 **CHAMPWAY** 冠泰電子有限公司
 CHAMPWAY ELECTRONICS CO., LTD.

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 52 (SERIES)
Ⓐ	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差): 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
Ⓑ					
Ⓒ					
Ⓓ					
Ⓔ					

TITLE 圖名	MULTI-PORTS RJ45 SIDE ENTRY PCB JACK		UNIT 單位	mm inch
PART NO. 料號	5288-B * *		SCALE 比例	1 : 1
REV. 版本	A.1	DATE 日期	2007-04-14	
CHECKED BY 審核	Michael		DRAWN BY 製圖	Valiant